



APTEK PoE Injector

Model: AP-POE48-2.5G-GE60

Datasheet

CÔNG TY TNHH CÔNG NGHỆ THÔNG TIN AN PHÁT

ĐC: 286/1 Trần Hưng Đạo, Phường Nguyễn Cư Trinh, Quận 1, TP. HCM

ĐT: 028 3925 3789 - Hotline HTKT: 1900 633 641

website: www.aphat.vn

Introduction

The PoE Injector is a single port PoE injector offer a compact and cost effective. It can convert standard 110~240V AC power into low voltage DC that runs over existing LAN cable to power up 60W. compliant network accessories. Remote powering of wireless LAN(WAN) access points, IP Security cameras, VoIP telephone and other low port density installations.

The PoE Mid-spans no need to connect with external power supply and its associated AC/DC power cabling, providing a compact, affordable, safe and reliable power soluion over existing ether infrastructure.

Features

- Up to 60W of Power (802.11af/at/bt)
- Supports 10/100/1000/2500Mbps applications
- Internal AC/DC converter no need for external power brick
- Easy plug-and-play installation
- Multi-protection

Application

- Use PoE Injector with PD to expand your network to where there are no power lines or outlets, where you wish to fix devices such as Aps, IP Cameras or IP Phones, etc.

Specifications

Model	AP-POE48-2.5G-GE60
Port	PoE/Link: 10/100/1000/2500Mbps adaptive RJ45 port output
	Link: 10/100/1000/2500Mbps adaptive RJ45 port input
LED indicator	PoE power indication
Network media	10/100/1000Base-TX: Category 5 and above unshielded twisted pair
Function	Compatible with plug and play of power receiving equipment conforming to IEEE 802.3af/at/bt standard
PoE Power Supply Agreement	IEEE 802.3af/at/bt
Network rate	10/100/1000/2500Mbps adaptive
PoE power transmission distance	≤100Meter
Input voltage	110-240VAC 50/60Hz
Output voltage	DC: 55V / ±0.5V
Output current	1.1A
Output power	60W
Lightning surge protect	4KV
Working environment	Operating temperature: -10 ~ 55 °C
Size	167mm x 57mm x 40mm (L x W x H)